



STRATO VEROSA LIME PAINT

O1



Product Training

For All Industry Professionals

suzuka.com.my/career-training



WALL FINISH PROFESSIONALS



suzuka.com.my

f O suzuka.group | Hotline : +6012-258 7388

Photos of the products shown in this catalogue may vary in color due to lighting condition & printing. We suggest you examine actual product samples before ordering.













SVR-E1-2504







SVR 101 - 118

A natural, eco-friendly lime paint made from pure lime and inorganic pigments, offering a beautiful matte finish.

It's breathable and perfect for interior wall surfaces. Suitable for homes, offices, cafes, restaurants and commercial building.

Appearance

Low Sheen

High Sheen

Smooth Texture





Rough Texture

Matte





Metallic

Features



Low VOC & Odor



Natural Composition & Eco-friendly



Formaldehyde & Lead Free





Non-toxic



Coverage



Non Powdery



Easy Application & DIY Friendly



Applicable on Ceiling





Easy Maintenance



Matte Finish

Complies to the

- American California Proposition 65 Standards
- LEED, U.S. Green Building Council Standards

Create two different patterns with **STRATO VEROSA** using different tools and techniques!



SVR-101 Galactic Grey







SVR-103 Cotton Foil











SVR-105 Lucent Moon






SVR-107 Gypsum Sands



SVR-108 Birch Paper



SVR-109 Caramel Clay



SVR-110 Bright Beige



SVR-111 Blonde Creme



All color shown are as close to the actual Suzuka® Strato® colors as modern printing techniques permit, nonetheless, there are still color/tone

We highly recommend seeing actual samples before ordering.


























SVR-116 Dusk Dew



SVR-117 Classic Taupe



SVR-118 Terra Cotta



All color shown are as close to the actual Suzuka® Strato® colors as modern printing techniques permit, nonetheless, there are still color/tone differences.

We highly recommend seeing actual samples before ordering.



SEALER **PRO** WALL SEALER PRO WALL SEALER PRO WALL SEALER PR

Superior primer for concrete, skimmed or masonry surfaces.

This sealer that has good substrate penetration abilities to increase adhesion of product to prevent chalking or peeling off. It has excellent alkaline resistance properties that can prevent efflorescence. It is an ideal base coat for any SUZUKA® or any wall finish products.

5L



Pressure

210 psi/150kg/cm²



m²/l/coat

Suitable for: Masonry wall

6.5 - 8.5

- Brickwork
- Plaster
- Skimmed Coat
- Asbestos free substrate
- Extremely good penetration.
 - Excellent adhesion. · Exterior and interior use.
 - · Applicable with brush, roller or spray gun.

Surface Dry : 1 Hard Dry : 5 Recoating : 5

• Excellent alkaline resistance to prevent efflorescence.

· Prevents skim coat from chalking & peeling off.

Substrate Temperature: 23°C - 26°C

• Good for new walls and repainting.

Nozzle Spray Angle Degree 1.8 - 2.0 mm 65° - 80°

Application Technique



Preparation:

- Surface shall be dry and free form dirt, oil, grease and foreign matters.
- Surface unevenness, crock, and the like shall be treated with cement filler.
- Primer is required for stained or painted surface with color other than white.

IMPORTANT:

Color may vary on application technique & amount of material used.

Dilution Guide:

Primer: Max 3% of clean water | Texture: Do not dilute.



Primer (Optional)

Roll 1-2 layers of primer on the entire surface. Allow 1 hour to dry between the layers.

Tool: Roller

Texture Coat Options Texture Coat Sponge Pattern 2B Brush Pattern



(1) Dampen the sponge with water and wring out excess moisture. This helps the paint spread more evenly and prevents it from soaking too deeply into the sponge.

(2) Lightly dip the sponge into the paint, ensuring it picks up a small, even amount. Avoid overloading the sponge with paint.



(3) Gently press the sponge onto the surface, using a light circular motion.

Start at the top of the wall and work your way down in sections. Overlap each stipple slightly to blend the edges & avoid harsh lines. Rotate the sponge occasionally to vary the pattern & prevent repetitive textures.



Apply 2 layers & let dry for 1-2 hours between coats.

(4) For the final layer, lightly dampen the sponge with Strato Verosa and gently rub in random circulation motions to enhance the

Let to fully dry in 24 hours.



(1) Work the paint into the surface using cross-hatch strokes (a combination of vertical and horizontal strokes).

Apply 2 layers.

Let dry for 1-2 hours between coats and to fully dry in 24 hours.



Recommended Tools: Roller, Brush & Sponge



Packing Data

Material	Packing	Coverage (per liter / ±5%)
Strato Primer Natural (Optional)	1 L	7 - 9 sqm
	4 L	28 - 36 sqm
Strato Verosa Texture Coat	1 L	6 - 8 sqm
	4 L	24 - 32 sqm

^{*} Primer & Texture Coat are sold separately

10